

TENOR AUDIO 350 M ET 350 M HAUTE-PUISSANCE STEREO AMPLIFIERS

Amplifier Type: Mono Block Power Amplifier

Chassis: Single

Dual Mono: Yes - Separate Channel per Chassis

Harmonic Structural Integrity: Yes

Voltage gain: 32 dB Unbalanced / 30 dB Balanced

350M Rated power: 2, 4, 8Ω, 1kHz, 220 VAC*: 1400, 700, 350 W

350M HP Rated power: 2, 4, 8Ω, 1kHz, 220 VAC*: 1500, 950, 500 W

S/N Ratio reference to 10 W*: -94 dBA

S/N Ratio reference to rated output*: -115 dBA

Frequency response: 3 to 200 000 Hz ± 3dB

THD + N @ 5 W 20-20K: < 0.05%

THD + N @ 10 W: < 0.04%*

THD + N @ 350 W: < 0.17%*

IMD SMPTE @ 10W - 100W: <.01%-.02%

Maximum output current per channel, 1kHz, 2 Ohm: 40A peak

Input impedance 1kHz Bal. / Unbal.: 20 KΩ / 33KΩ

350M Damping factor*: 100

350M HP Damping factor*: 200

Weight per unit: 118 lbs / 53.5 kg

Shipping weight in custom road case: 148 lbs / 67.2 kg

Dimensions: 19.5" W x 28" D (including connectors) x 9.5" H (including top ventilation)

* : @ 8 Ohm, 1kHz

March 2019

Tenor Inc. reserves the right to make improvements without notice that may result in specification changes

